PAY-OFF ®

OXY – FITE 568

Oxy - fite 568 is an inorganic oxygen scavenger, in powder form, whose activity is based on the reaction between sulfite ions and free oxygen which is found in feed water (TDO).
Each molecule reacts with one half molecule oxygen according to underneath equation :
$2SO_3 = + O_2 = SO_4$

How to use :

Oxy - fite 568 can be mixed with boiler water treatment chemicals in the dosing tank.
Dosage : 8,07 gram oxy-fite 568 for each gram of TDO.

Oxy-fite 568 adalah suatu oxygen scavenger anorganik dalam bentuk padat aktifitasnya berdasarkan reaksi antara ion sulfite dan oxygen bebas yang terdapat di dalam feed water (TDO). Setiap molekul bereaksi dengan setengah molekul oxygen sesuai persamaan :
$2SO_3 = + O_2 = SO_4$

Cara penggunaan :

Oxy-fite 568 dapat dicampur dengan boiler water treatment dalam dosing tank.
Dosage : 8,07 gram oxy-fite for each gram of TDO.

PT. PUJI LESTARI PURNAMA
Ready Sentra Cimone Blok B No.15 - 16 Jl. Jend. Gatot Subroto KM. 2, Cimone - Tangerang 15114
Telp. : (62-21) 55795815, 5587777 (Hunting) Fax. : (62-21) 55795816